

# OKO-TEC-SYSTEMS

## Complete Set of Double Tube Boom / Order Number 2002

<u>article</u>	<u>quantity</u>	<u>material</u>	<u>size</u>	<u>weight</u>
150 m double tube boom, white, printed Ø 40 cm und 20 cm	1	polyethylene 220 µ	lying flat width 1000 mm	52 kg
clamps	2	polyethylene	1000x250 mm	12 kg
couplings* B 2 ½ "	4	aluminium		
blind aluminium coupling	4	aluminium		
uncoiling reel with removable side component for introducing hose change	1	metal, painted red	Ø 440 mm length 1120 mm	18 kg
protective foil, black with Velcro band	1	PVC awning cloth	1125 x 1075 mm	0,8 kg
storage and transport bag	1	PVC	750 x 570 x 430 mm	1,5 kg
sealing source in the metering bucket	1	polymer		10 kg
practice double tube boom to spare application material	1	polyethylene,	30 m	10 kg

### polyethylene quality features

specially treated, anti-static and UV-resistant  
 - thickness 200 µ DIN 53 370  
 - high shock resistance ASTM D 1706-67  
 - can be stored over long periods DIN 53 497  
 - high tearing resistance DIN 53 455

- elastic in conformity with DIN 53 445  
 even at lower temperatures  
 - high chemical resistance  
 - antistatic treatment  
 - environmentally friendly disposal

### special accessories

### order number

150 m substitute double tube boom	2020
benzine air blower	2021
30 m practice hose	2022
stable-shape aeration hose	2023
PVC transport sack for clamps	2024
protective UV foil with Velcro seal	2025
connecting element for use in water	2026
substitute uncoiling reel	2027
sealing source in the 10 kg metering bucket	2028
2 PE clamps including drive screws and couplings	2029
20 m B-hose including couplings	2030

ball cock with moving tappet component	at request
stainless steel couplings and ball cocks	at request
stainless steel exhaust gas injector	at request

\*Storz, Guillemin or Instantaneous couplings